vsf fahrradmanufaktur®
Premium Mobilität

GX-500

SRAM Apex XPLR 12-speed / Disc

Article	Inch	Frame size	Color
102420548	28"	Gents, 48 cm	dry terracotta glossy
102420551	28"	Gents, 51 cm	dry terracotta glossy
102420554	28"	Gents, 54 cm	dry terracotta glossy
102420557	28"	Gents, 57 cm	dry terracotta glossy
102420560	28"	Gents, 60 cm	dry terracotta glossy

Technical changes and changes in equipment reserved, color deviations possible.

General	**Frame**	25 CrMo 4, double butted
	Head set	Acros AZX-228, 1 1/8"-1,5", External Cup
	Fork	vsf fm Gravel 28" aluminum, 12 x 100 mm, Flatmount, tapered
	Shifting System	SRAM Apex XPLR , 12-speed
	Derailleur	- - -
	Brakes	SRAM Apex (front 160 mm / rear 160 mm), Flatmount
	Headlight	---
	Rear light	- - -
	Carrier	- - -
	Saddle	Selle Italia Model Y
	Seat post	Ritchey WCS Carbon Link Flexilogic, 27,2 mm, 350 mm
	Pedals	- - -
	Kickstand	- - -
	Chainguard	- - -
	Mudguard	- - -
	Other	max load 120 kg, vsf fahrradmanufaktur Enamel-Mug
	Weight	11,5 kg
Cockpit	**Stem**	Levelnine, aluminum, 6°, (90 / 90 / 90 / 110 / 110 mm)
	Handlebars	Levelnine Gravel, aluminum, Flare 12°, (440 / 440 / 440 / 460 / 480 mm)
	Grips	Fizik Vento Solocush Tacky handlebar tape, 2,7 mm thick, black
	Shift lever	SRAM Apex, 12-speed
	Brake lever	SRAM Apex, 12-speed
Wheels/Tires/Drivetrain	**Tires**	Schwalbe G-One R, 45-622
	Rims	Ryde DP19, Disc, 32 holes
	Spokes	Niro 2,0 mm black
	Front Hub	KT, 12 x 100 mm, Centerlock, 32 holes
	Rear Hub	KT, 12 x 142 mm , Centerlock, 32 holes
	Sprocket	SRAM XPLR PG-1231, 12-speed, 11-44 teeth
	Chain	SRAM Apex, 12-speed
	Inner bearing	SRAM DUB, BSA
	Bottom bracket	SRAM Apex, 40 teeth, 170 mm
	Gear ratio (f:r)	40 teeth : 11-44 teeth