



GX-800

Shimano GRX Di2 RX825 12-speed / disc

Article	Inch	Frame size	Color
102620101	28"	Gents, 48 cm	midnight glossy
102620102	28"	Gents, 51 cm	midnight glossy
102620103	28"	Gents, 54 cm	midnight glossy
102620104	28"	Gents, 57 cm	midnight glossy
102620105	28"	Gents, 60 cm	midnight glossy

Technical changes and changes in equipment reserved, color deviations possible.

Category	Specification	
General	Frame	Reynold 725, Chrome-Moly, suspension-fork-ready
	Head set	Acros AZX-228, 1 1/8"-1,5", external cup
	Fork	vsf fm Gravel carbon, 12 x 100 mm, flatmount, tapered
	Shifting System	Shimano GRX Di2 RD-RX827-SGS, 12-speed
	Derailleur	---
	Brakes	Shimano GRX BR-RX820 (front 160 mm / rear 160 mm), flatmount
	Headlight	---
	Rear light	---
	Carrier	---
	Saddle	SQlab 611
	Seat post	Ritchey WCS Carbon Link Flexilogic, 27.2 mm, 350 mm
	Pedals	Marwi SP-102, flat pedal, aluminium, black
	Kickstand	---
	Chainguard	---
	Mudguard	---
Other	max load 130 kg	
Weight	9,9 kg	
Cockpit	Stem	Levelnine, aluminium, 6°, (75 / 75 / 90 / 90 / 110 mm)
	Handlebars	Levelnine Pro Team Gravel, carbon, Flare 16°, (420 / 420 / 440 / 440 / 440 mm)
	Grips	Fizik Vento Solocush Tacky, black
	Shift lever	Shimano GRX Di2 ST-RX825, 1-/12-speed
	Brake lever	Shimano GRX Di2 ST/BL-RX825, 1-/12-speed
Wheels/Tires/Drivetrain	Tires	Schwalbe G-One R/RS Pro Evo V-Guard, 50-622
	Rims	Newmen Adadvanced, Carbon, 25 x 622
	Spokes	Newmen black
	Front Hub	Newmen Advanced, 12 x 100 mm, Centerlock
	Rear Hub	Newmen Advanced, 12 x 142 mm, Centerlock, Microspline
	Sprocket	Shimano XT CS-M8200, 12-speed, 10-51 teeth
	Chain	Shimano XT CN-M8100, 12-speed
	Inner bearing	Shimano SM-BBR60, für Hollowtec II, BSA
	Bottom bracket	Shimano GRX FC-RX820-1, Hollowtech II, 42 teeth, (170 / 170 / 172,5 / 172,5 / 175 mm)
	Gear ratio (f:r)	42 teeth : 10-51 teeth