



GX-600

Shimano GRX RX822 12-speed / disc

Article	Inch	Frame size	Color
102620111	28"	Gents, 48 cm	emerald matt
102620112	28"	Gents, 51 cm	emerald matt
102620113	28"	Gents, 54 cm	emerald matt
102620114	28"	Gents, 57 cm	emerald matt
102620115	28"	Gents, 60 cm	emerald matt

Technical changes and changes in equipment reserved, color deviations possible.

General	
Frame	25 CrMo 4, double butted, suspension-fork-ready
Head set	Acros AZX-228, 1 1/8"-1,5", external cup
Fork	vsf fm Gravel carbon, 12 x 100 mm, flatmount, tapered
Shifting System	Shimano GRX RD-RX822-SGS, 12-speed
Derailleur	---
Brakes	Shimano GRX BR-RX410 (front 160 mm / rear 160 mm), flatmount
Headlight	---
Rear light	---
Carrier	---
Saddle	SQlab 611
Seat post	Ritchey WCS Carbon Link Flexilogic, 27.2 mm, 350 mm
Pedals	Marwi SP-102, flat pedal, aluminium, black
Kickstand	---
Chainguard	---
Mudguard	---
Other	max load 130 kg
Weight	11,2 kg
Cockpit	
Stem	Levelnine, aluminium, 6°, (75 / 75 / 90 / 90 / 110 mm)
Handlebars	Levelnine Gravel, aluminium, Flare 12°, (420 / 420 / 440 / 440 / 440 mm)
Grips	Fizik Vento Solocush Tacky, black
Shift lever	Shimano GRX ST-RX610, 1-/12-speed
Brake lever	Shimano GRX ST/BL-RX610, 1-/12-speed
Wheels/Tires/Drivetrain	
Tires	Schwalbe G-One R Raceguard, 50 x 622, TLE
Rims	Newmen Performance 30 Light, 28 holes, tubeless-ready
Spokes	Niro, black
Front Hub	Shimano HB-TC500, Centerlock, 28 holes
Rear Hub	Shimano SLX FH-TM7110, Centerlock, 28 holes, Microspline
Sprocket	Shimano SLX CS-M7100, 12-speed, 10-51 teeth
Chain	Shimano SLX CN-M7000, 12-speed
Inner bearing	Shimano BB-MT501B, für Hollowtec II, BSA
Bottom bracket	Shimano GRX FC-RX610-1, Hollowtech II, 40 teeth, (170 / 170 / 172,5 / 172,5 / 175 mm)
Gear ratio (f:r)	40 teeth : 10-51 teeth