



## GX-400

Shimano Cues U6000 2 x 10-speed / disc

Article	Inch	Frame size	Color
102620121	28"	Gents, 48 cm	ebony matt
102620122	28"	Gents, 51 cm	ebony matt
102620123	28"	Gents, 54 cm	ebony matt
102620124	28"	Gents, 57 cm	ebony matt
102620125	28"	Gents, 60 cm	ebony matt
102620131	28"	Gents, 48 cm	black olive glossy
102620132	28"	Gents, 51 cm	black olive glossy
102620133	28"	Gents, 54 cm	black olive glossy
102620134	28"	Gents, 57 cm	black olive glossy
102620135	28"	Gents, 60 cm	black olive glossy

Technical changes and changes in equipment reserved, color deviations possible.

General	<b>Frame</b>	25 CrMo 4, double butted, suspension-fork-ready
	<b>Head set</b>	Acros AZX-228, 1 1/8"-1,5", external cup
	<b>Fork</b>	vsf fm steel, 12 x 100 mm, Flatmount, tapered
	<b>Shifting System</b>	Shimano Cues RD-U6020-10, 10-speed
	<b>Derailleur</b>	Shimano Cues FD-U6030, 2-speed
	<b>Brakes</b>	Shimano Cues BR-U6030 (front 160 mm / rear 160 mm), flatmount
	<b>Headlight</b>	---
	<b>Rear light</b>	---
	<b>Carrier</b>	---
	<b>Saddle</b>	Selle Italia Model Y
	<b>Seat post</b>	Ritchey WCS Carbon Link Flexilogic, 27.2 mm, 350 mm
	<b>Pedals</b>	Marwi SP-450, flat pedal, black
	<b>Kickstand</b>	---
	<b>Chainguard</b>	---
<b>Mudguard</b>	---	
<b>Other</b>	max load 140 kg	
<b>Weight</b>	12,9 kg	
Cockpit	<b>Stem</b>	Levelnine, aluminium, 6°, ( 75 / 75 / 90 / 90 / 110 mm)
	<b>Handlebars</b>	Levelnine Gravel, aluminium, Flare 12°, (420 / 420 / 440 / 440 / 440 mm)
	<b>Grips</b>	Fizik Vento Solocush Tacky, black
	<b>Shift lever</b>	Shimano Cues ST-U6030, 2-/10-speed
	<b>Brake lever</b>	Shimano Cues ST-U6030, 2-/10-speed
Wheels/Tires/Drivetrain	<b>Tires</b>	Schwalbe G-One Comp K-Guard, 45 x 622
	<b>Rims</b>	Mach1 Cross-R23, 622x23C, 32 holes, tubeless-ready
	<b>Spokes</b>	Niro, black
	<b>Front Hub</b>	Shimano HB-TC500, Centerlock, 32 holes
	<b>Rear Hub</b>	Shimano FH-TC500, Centerlock, 32 holes
	<b>Sprocket</b>	Shimano CS-LG300-10, 10-speed, 11-39 teeth
	<b>Chain</b>	Shimano CN-LG500
	<b>Inner bearing</b>	Shimano BB-MT501B, für Hollowtec II, BSA
	<b>Bottom bracket</b>	Shimano Cues FC-U6030-2, Hollowtech II, 46/32 teeth, (170 / 170 / 172,5 / 172,5 / 175 mm)
<b>Gear ratio (f:r)</b>	46/32 teeth : 11-39 teeth	