



## GXQ-400

Shimano Cues U6000 2 x 10-speed / disc

Article	Inch	Frame size	Color
102620171	28"	Gents, 48 cm	ebony matt
102620172	28"	Gents, 51 cm	ebony matt
102620173	28"	Gents, 54 cm	ebony matt
102620174	28"	Gents, 57 cm	ebony matt
102620175	28"	Gents, 60 cm	ebony matt
102620181	28"	Gents, 48 cm	cosmic silver glossy
102620182	28"	Gents, 51 cm	cosmic silver glossy
102620183	28"	Gents, 54 cm	cosmic silver glossy
102620184	28"	Gents, 57 cm	cosmic silver glossy
102620185	28"	Gents, 60 cm	cosmic silver glossy

Technical changes and changes in equipment reserved, color deviations possible.

General	
<b>Frame</b>	25 CrMo 4, double butted, suspension-fork-ready
<b>Head set</b>	Acros AZX-228, 1 1/8"-1,5", external cup
<b>Fork</b>	vsf fm steel, 12 x 100 mm, Flatmount, tapered
<b>Shifting System</b>	Shimano Cues RD-U6020-10, 10-speed
<b>Derailleur</b>	Shimano Cues FD-U6030, 2-speed
<b>Brakes</b>	Shimano Cues BR-U6030 (front 160 mm / rear 160 mm), flatmount
<b>Headlight</b>	Busch & Müller Lumotec Dopp N Plus, 35 LUX
<b>Rear light</b>	Trelock, LS654
<b>Carrier</b>	Racktime Light-it
<b>Saddle</b>	Selle Italia Model Y
<b>Seat post</b>	Ritchey WCS Carbon Link Flexilogic, 27.2 mm, 350 mm
<b>Pedals</b>	Marwi SP-450, flat pedal, black
<b>Kickstand</b>	Atran Velo Parko
<b>Chainguard</b>	---
<b>Mudguard</b>	SKS B55, plastic
<b>Other</b>	max load 140 kg
<b>Weight</b>	14,7 kg
Cockpit	
<b>Stem</b>	Levelnine, aluminium, 6°, ( 75 / 75 / 90 / 90 / 110 mm)
<b>Handlebars</b>	Levelnine Gravel, aluminium, Flare 12°, (420 / 420 / 440 / 440 / 440 mm)
<b>Grips</b>	Fizik Vento Solocush Tacky, black
<b>Shift lever</b>	Shimano Cues ST-U6030, 2-/10-speed
<b>Brake lever</b>	Shimano Cues ST-U6030, 2-/10-speed
Wheels/Tires/Drivetrain	
<b>Tires</b>	Schwalbe G-One Comp K-Guard, 45 x 622
<b>Rims</b>	Mach1 Cross-R23, 622x23C, 32 holes, tubeless-ready
<b>Spokes</b>	Niro, black
<b>Front Hub</b>	Shutter Precision PL-7, 12 x 100 mm, hub dynamo, Centerlock, 32 holes
<b>Rear Hub</b>	Shimano FH-TC500, Centerlock, 32 holes
<b>Sprocket</b>	Shimano CS-LG300-10, 10-speed, 11-39 teeth
<b>Chain</b>	Shimano CN-LG500
<b>Inner bearing</b>	Shimano BB-MT501B, für Hollowtec II, BSA
<b>Bottom bracket</b>	Shimano Cues FC-U6030-2, Hollowtech II, 46/32 teeth, (170 / 170 / 172,5 / 172,5 / 175 mm)
<b>Gear ratio (f:r)</b>	46/32 teeth : 11-39 teeth